

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** AS-202 FIRE RETARDANT SILICONE SEALANT

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC1: Adhesives, sealants.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Aseal Marketing Sdn. Bhd.  
Lot 2291, Jalan Kampung Baru,  
Kampung Baru Sungai Buloh  
Sungai Buloh  
Selangor  
47000  
Malaysia

**Tel:** +603-61579698

**Fax:** +603-61578002

**Email:** info@alsealmarketing.com

**1.4. Emergency telephone number**

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Eye Dam. 1: H318; Skin Sens. 1: H317

**Most important adverse effects:** May cause an allergic skin reaction. Causes serious eye damage.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.

**Hazard pictograms:** GHS05: Corrosion  
GHS07: Exclamation mark



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 2

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P362+P364: Take off contaminated clothing and wash it before reuse.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### LIMESTONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-279-6	1317-65-3	Substance with a Community workplace exposure limit.	-	10-30%

##### VINYLTRIS(METHYLETHYLKETOXIME)

218-747-8	2224-33-1	-	Skin Sens. 1: H317; STOT RE 2: H373; Eye Dam. 1: H318	1-10%
-----------	-----------	---	---	-------

##### SILICA, AMORPHOUS

231-545-4	7631-86-9	Substance with a Community workplace exposure limit.	-	1-10%
-----------	-----------	--	---	-------

##### METHYLTRIS(METHYLETHYLKETOXIME) - REACH registered number(s): 01-2119970560-38-0003

245-366-4	22984-54-9	-	STOT RE 2: H373; Eye Irrit. 2: H319; Skin Sens. 1: H317	1-10%
-----------	------------	---	---	-------

##### N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

217-164-6	1760-24-3	-	Eye Dam. 1: H318; Skin Sens. 1B: H317	<1%
-----------	-----------	---	---------------------------------------	-----

##### DIBUTYLTIN DILAURATE

201-039-8	77-58-7	-	Muta. 2: H341; Repr. 1B: H360FD; STOT RE 1: H372	<1%
-----------	---------	---	--	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 3

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS.  
Do not create dust.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

[cont...]

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 4

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Hazardous ingredients:

LIMESTONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	4 mg/m <sup>3</sup>	-

### DNEL/PNEC Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Insoluble

**Viscosity:** No data available.

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 1.3

**VOC g/l:** No data available.

**Melting point/range°C:** Not applicable.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** Not applicable.

[cont...]

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 5

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

##### LIMESTONE

ORAL	RAT	LD50	2000	mg/kg
------	-----	------	------	-------

##### VINYLTRIS(METHYLETHYLKETOXIME)

DERMAL	RAT	LD50	2009	mg/kg
ORAL	RAT	LD50	2000	mg/kg

##### SILICA, AMORPHOUS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>10000	mg/kg

##### METHYLTRIS(METHYLETHYLKETOXIME)

DERMAL	RAT	LD50	2000	mg/kg
--------	-----	------	------	-------

[cont...]

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 6

ORAL	RAT	LD50	2453	mg/kg
------	-----	------	------	-------

## N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

DERMAL	RBT	LD50	2000	mg/kg
DUST/MIST	RAT	4H LC50	1.49	mg/l
ORAL	RAT	LD50	2295	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

##### LIMESTONE

Daphnia magna	48H EC50	100	mg/l
FISH	96H LC50	100	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	14	mg/l

##### VINYLTRIS(METHYLETHYLKETOXIME)

Daphnia magna	48H EC50	201	mg/l
FISH	96H LC50	1011	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	19.19	mg/l

##### SILICA, AMORPHOUS

DAPHNIA	24H EC50	>10000	mg/l
FISH	96H LC50	>10000	mg/l

[cont...]

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 7

## METHYLTRIS(METHYLETHYLKETOXIME)

Daphnia magna	48H EC50	231.84	mg/l
FISH	96H LC50	972.34	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	18.45	mg/l

## N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

Daphnia magna	48H EC50	81	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	8.8	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	597	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

# SAFETY DATA SHEET

AS-202 FIRE RETARDANT SILICONE SEALANT

Page: 8

## Section 16: Other information

### Other information

**Other information:** according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H341: Suspected of causing genetic defects.  
H360FD: May damage fertility. May damage the unborn child.  
H372: Causes damage to organs through prolonged or repeated exposure.  
H373: May cause damage to organs ([blood]) through prolonged or repeated exposure ([oral]).

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.